


DIP TYPE



■ MATERIAL

INSULATOR: PBT +30% GLASS FIBER (UL94V-0).
 CONTACT: PHOSPHOR BRONZE OR BRASS.
 PLATING: GOLD OVER NICKEL.

■ SPECIFICATION

CURRENT RATING: 3 AMP.
 INSULATION RESISTANCE: 5000 MEGOHMS MIN AT 500 VDC.
 CONTACT RESISTANCE: 20 MILLIOHMS MAX.
 VOLTAGE : 500V FOR ONE MINUTE.

■ ENVIRONMENTAL

TEMPERATURE RANGE: -40°C TO +105°C.

KE-DXE-12EA-LF
 LEADFREE
 RoHS Compliant



Allconnectors

www.allconnectors.de
 Tel.: 0049 711 7009503
 30/31 Hilderstadt - Germany

info@allconnectors.de
 Fax: 0049 711 7009504
 Kettnerstr. 25

PART NO. KE-DXE-12EA

DWG NO. KE-DXE-12EA

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2
 .XX ±
 .XXX ±
 AWG

DESCRIPTION: 3.96 PITCH WITH OUT MOUNTING EAR

AREA

REVISIONS

HK

DATE