


DIP TYPE



KE-DXE-xx-LF
LEADFREE

- MATERIAL
INSULATOR: PBT +30% GLASS FIBER (UL94V-0).
CONTACT: PHOSPHOR BRONZE OR BRASS.
PLATING: GOLD OVER NICKEL.

- SPECIFICATION
CURRENT RATING: 3 AMP.
INSULATION RESISTANCE: 5000 MEGOHMS MIN AT 500 VDC.
CONTACT RESISTANCE: 20 MILLIOHMS MAX.
VOLTAGE : 500V FOR ONE MINUTE.

- ENVIRONMENTAL
TEMPERATURE RANGE: -40°C TO +105°C.

Circuit	Dimension		
	A	B	C
10	15.84	24.06	27.40
12	19.80	28.02	31.36
16	27.72	35.94	39.28
20	35.64	43.86	47.20
24	43.56	51.78	55.12
26	47.52	55.74	59.08
28	51.48	59.70	63.04
30	55.44	63.66	67.00
32	59.40	67.62	70.96
36	67.32	75.54	78.88
40	75.24	83.46	86.80
44	83.16	91.38	94.72
46	87.12	95.34	98.68
50	95.04	103.26	106.60
56	106.92	115.14	118.48
60	114.84	123.06	126.40
62	118.80	127.02	130.36
64	122.76	130.98	134.32
70	134.64	142.86	146.20
72	138.60	146.82	150.16

RoHS Compliant

Allconnectors
www.allconnectors.de
Tel.: 0049 711 7005903
70 794 Hilderstadt - Germany

info@allconnectors.de
Fax: 0049 711 7005904
Kettenerstr. 25

PART NO. KE-DXE-xx

DWG NO. KE-DXE-xx

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X±0.2
.XX±
XXX±
AWG

DESCRIPTION:

3.96 PITCH WITH OUT MOUNTING EAR

AREA

REVISIONS

HK

DATE