


DIP TYPE



■ MATERIAL  
 INSULATOR: PBT GLASS FIBER (UL94V-0).  
 CONTACT: BRASS  
 PLATING: GOLD OVER NICKEL.

■ SPECIFICATION  
 CURRENT RATING: 3 AMP.  
 INSULATION RESISTANCE: 5000 MEGOHMS MIN AT 500 VDC.  
 CONTACT RESISTANCE: 20 MILLIOHMS MAX.  
 VOLTAGE : 500V FOR ONE MINUTE.

■ ENVIRONMENTAL  
 TEMPERATURE RANGE: -40°C TO +125°C.

UNLESS OTHERWISE SPECIFIED	
0-10 ±0.2	10-30 ±0.3
30-100 ±0.4	100-300 ±0.5
OVER 300 ±0.6	ANGULAR ±0.5°

KE-DXExyyy-20M13-LF  
 BLANK:3.96mm LEADFREE  
 5:5.08mm BLANK:4.8mm  
 D33:3.3mm

RoHS Compliant



**All Connectors**

www.allconnectors.de info@allconnectors.de  
 Tel.: 0049 711 709508 Fax: 0049 711 709504  
 70794ilderstadt - Germany Kettamerstr. 25

PART NO. KE-DXExyyy-20M13

DWG NO. KE-DXExyyy-20M13

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X±  
 .XX±  
 .XXX±  
 AWG

DESCRIPTION:

3.96 PITCH WITH OUT MOUNTING EAR

AREA

REVISIONS

HK

DATE