



NOTE:
 MATERIAL:
 HOUSING:THERMOPLASTIC(NYLON+GF)
 CONTACT:BRASS
 PLATING:
 CONTACT: GOLD PLATING
 SPECIFICATION:
 VOLTAGE RATING: 50V
 CURRENT RATING: 1.1A
 CONTACT RESISTANCE TERMINAL:20m Ω MAX
 DIELECTRIC WITHSTANDING VOLTAGE:500V AC
 INSULATION RESISTANCE:1000M Ω MIN

RECOMMENDED MODULE LAYOUT

All Connectors
 www.allconnectors.de
 Tel.: 0049 711 7009503
 70794 Filderstadt - Germany

info@allconnectors.de
 Fax: 0049 711 7009504
 Kettnerstr. 25

RoHS Compliant		TOLERANCES ARE	
DRAWING BY CY		X ±	
CHECKED BY GENIUS		.X ±	
UNIT/ mm	SCALE 1 : 1	.XX ±	
DATE		.XXX ±	
SIZE A4	PJECTION	ANG ±	



ORDER INFORMATION

PCIX-E-16436L8R-LF

```

  graph TD
    Root[PCIX-E-16436L8R-LF] --> S[SERIES]
    Root --> EC[EDGE CLIP]
    Root --> W[164WAY]
    Root --> LF[LEADFREE]
    W --> R8[RIGHT 8 WAY]
    W --> L36[LEFT 36WAY]
  
```

DESCRIPTION: PCI 1.0 164Y 旋轉夾板 式成品