

Specifications


Current Rating: 1Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 300V AC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C

Materials

Contact Material: Phosphor Bronze
 Insulation Material: Polyester, UL 94V-0
 LCP \triangle
 All materials must meet Greenconn requirement for environment protection

Recommended P.C.B. Layout



(Tolerance: ± 0.05)



Ordering Information

HFJDS4Y - XX XX XXX L

 No. of Pins Per Row: 03-50
 Standard Plating: 01=Gold Flash, 02=Gold 3U", 11=Tin, XX=Select Plating
 Pin Length: 001=2.4, XXX=Select A
 Material: L=LCP, T=6T

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE	 www.allconnectors.eu info@allconnectors.eu Tel. +49 (0)711 / 358 110 20 Fax +49 (0)711 / 358 110 25	
X. ± 0.38 .XX ± 0.25 .XXX ± 0.13	X' $\pm 5^\circ$.X' $\pm 2^\circ$.XX' $\pm 1^\circ$.XXX' $\pm 0.5^\circ$	Andy2005.08.12			
UNIT:mm	SCALE 1:1	APPRO.	DATE	PART NO (料号)	HFJDS4Y-XXXXXXL
A4 	SHEET: 1 of 1			DRAWING NO.(图号)	HFJDS4Y-01
					REV.A0