


Specifications

Current Rating: 2Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 500V AC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C

Materials

Contact Material: Phosphor Bronze
 Insulation Material: Polyester, UL 94V-0
 NYLON-6T
 All materials must meet Greconnc requirement for environment protection



Ordering Information

HFLDSV6E - XX XX XXX T W X

No. of Pins: 02-25
 Standard Plating: 01=Gold Flash, 02=Gold 3U", 11=In, XX>Select Plating
 Pin Length: 00=6.0, XXX>Select W
 Material: L=CP, T=NL6T
 Post: P=#1th Post, W=#without Post
 Packing: TR=Tube+Re11, T=tube

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE
X ±0.38 .X ±0.25 .XX ±0.13	X° ±5° X° ±2° .XX° ±1° .XXX° ±0.5°	Andy2005.08.12	
UNIT:mm	SCALE 1:1	CHECK	DATE
A4	SHEET: 1 of 1	APPRO.	DATE

All connectors www.allconnectors.eu info@allconnectors.eu Tel: +49 (0)711 358 110 20 Fax: +49 (0)711 358 110 25	
FILE NAME (品名)	2.0MM Female Header SMT TYPE
PART NO (料号)	HFLDSV6E-XXXXXXXXTWX
DRAWING NO. (图号)	HFLDSV6E-05
REV.AO	