



Recommended P.C.B. Layout

(Tolerance:0.05mm)

- Specifications
 Current Rating: 2Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 500V AC
 Contact Resistance: 20mΩ Max.
 Operating Temperature:-40°C to +105°C
- Materials
 Contact Material: Phosphor Bronze
 Cover Material: LCP UL94V-0,Color:Black.
 Housing Material: NY6T UL94V-0,Color:Black.
- All materials must meet Greenconn requirement for environment protection Δ

Ordering Information

HFLT55 H - XX XX XXX T

No. of Pins Per Row	Standard Plating	Pin Length	Material
02-40	01=Gold Flash 02=Gold 3U" 11=Fin XX=Select Plating	001 =8.35/2.1 XXX=Select A/B	L=LCP T=NL6T

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE	 <small>www.allconnectors.eu info@allconnectors.eu</small> <small>Tel. +49 (0)711 / 358 110 20 Fax +49 (0)711 / 358 110 25</small>
X. ± .X ±0.38 .XX ±0.25 .XXX ±0.13	X'. ±5' .X' ±2' .XX' ±1' .XXX' ±0.5'	Andy2005.08.12		
UNIT:mm	SCALE 1:1	CHECK	DATE	FILE NAME (品名)
A4	SHEET: 1 of 1	APPRO.	DATE	PART NO (料号)
				HFLT55H-XXXXXXXXT
				DRAWING NO.(图号)
				HFLT55H-01
				REV.A0