


Specifications

- Current Rating: 3Amp
- △ Insulation Resistance: 1000MΩ Min.
- Dielectric Withstanding: 600VAC
- △ Contact Resistance: 20mΩ Max.
- Operating Temperature: -40°C to +105°C

Materials

Contact Material: Phosphor Bronze
 Insulation Material: P. B. T, UL94V-0
 All materials must be GP materials




Recommended P.C.Board Hole Layout
 (Tolerance: ±0.05)

Ordering Information

HFNDS2 - XX XX XXX P

No. of Pins Per Row	Standard Plating	Pin Length	Material
02-40	01=Gold Flash 02=Gold 3U" 11=Tin XX=Select Plating	001 =3.0 XXX=Select A	L=LCP T=NL6T P=PBT

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE	 www.allconnectors.eu info@allconnectors.eu Tel. +49 (0)711 / 358 110 20 Fax +49 (0)711 / 358 110 25
		Andy2005.08.12		
.X ±0.38 .XX ±0.25 .XXX ±0.13	.X° ±5' .XX° ±2' .XXX° ±0.5'	CHECK	DATE	
UNIT:mm	SCALE 1:1	APPRO.	DATE	
A4	SHEET: 1 of 1	FILE NAME (品名)		2.54MM Female Header DIP TYPE
PART NO (料号)				HFNDS2-XXXXXXXXP
DRAWING NO (图号)				HFIDS2-01
				REV.AO