


Specifications

Current Rating: 3Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 600V AC/DC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C

Materials

Contact Material: Phosphor Bronze
 Insulation Material: Polyester, UL 94V-0
 For 02~24 pins, use the plastic of PBT, while 25~40 pins using Nylon6T +20% recycle plastic
 All materials must be GP materials

Recommended P.C.Board
 Hole Layout



Ordering Information

Ordering Information

HFNSR2 - XX XX XXX P

No. of Pins Per Row: 02-40
 Standard Plating: 01=Gold Flash, 02=Gold 3U", 11=Tin, XX=Select Plating
 Pin Length: 001=2.8, XXX=Select A
 Material: L=LCP, T=NL6T, P=PBT

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN DATE	 www.allconnectors.eu info@allconnectors.eu Tel. +49 (0)711 / 358 110 20 Fax +49 (0)711 / 358 110 25	
X. ± 0.38 .XX ± 0.25 .XXX ± 0.13	X' ± 5° .X' ± 2° .XX' ± 1° .XXX' ± 0.5°	Andy2005.08.12		
UNIT:mm	SCALE 1:1	CHECK DATE	FILE NAME (品名)	2.54MM Female Header R/A TYPE
A4	SHEET: 1 of 1	APPRO. DATE	PART NO (料号)	HFNSR2-XXXXXXXP
			DRAWING NO.(图号)	HFISR2-01
				REV.AO