

Specifications

Current Rating: 3Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 600V AC/DC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C


Materials

Contact Material: Phosphor Bronze
 Insulation Material: Polyester, UL 94V-0
 All materials must be GP materials

注: 02~24PIN塑膠材質用P.B.T料生產,
 25~40PIN塑膠材質用PA6T+20%料生產.

Recommended P.C.Board

Hole Layout



Ordering Information

HFNSS3 - XX XX XXX P

No. of Pins Per Row: 02-40

Standard Plating: 01=Gold Flash, 02=Gold 3U", 11=Tin, XX=Select Plating

Pin Length: 001=3.0, XXX=Select A

Material: L=LCP, T=NL6T, P=PBT

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE	All Connectors	
X. ±	X' ±5°	Andy2005.08.12		www.allconnectors.eu info@allconnectors.eu Tel. +49 (0)711 / 358 110 20 Fax +49 (0)711 / 358 110 25	
.X ±0.38	.X' ±2°	CHECK	DATE	FILE NAME (品名)	2.54MM Female Header DIP TYPE
.XX ±0.25	.XX' ±1°	APPRO.	DATE	PART NO (料号)	HFNSS3-XXXXXXXP
.XXX ±0.13	.XXX' ±0.5°			DRAWING NO.(图号)	HFISS3-01
UNIT:mm	SCALE 1:1			REV.	AO
A4	SHEET: 1 of 1				