


### Specifications

Current Rating: 3Amp  
 Insulation Resistance: 1000MΩ Min.  
 Dielectric Withstanding: 600V AC/DC  
 Contact Resistance: 20mΩ Max.  
 Operating Temperature: -40°C to +105°C

### Materials



Contact Material: Phosphor Bronze  
 Insulation Material: Polyester, UL 94V-0  
 P.B.T  
 All materials must be GP materials

### Recommended P.C.Board Hole Layout



### Ordering Information

HFNSS5U - XX XX XXX P  
  
 No. of Pins Per Row: 01=Gold Flash, 02=Gold 3U", 11=Tin, XX=Select Plating  
 Standard Plating  
 Pin Length: 001=3.0, XXX=Select A  
 Material: L=LCP, T=NL6T, P=PBT

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE	 <small>www.allconnectors.eu   info@allconnectors.eu Tel. +49 (0)711 / 358 110 20   Fax +49 (0)711 / 358 110 25</small>	
.X ± 0.38 .XX ± 0.25 .XXX ± 0.13	.X° ± 5° .X° ± 2° .XX° ± 1° .XXX° ± 0.5°	Andy2005.08.12			
UNIT:mm	SCALE 1:1	APPRO.	DATE	PART NO (料号)	HFNSS5U-XXXXXXXP
A4 	SHEET: 1 of 1			DRAWING NO.(图号)	HFISS5U-01
					REV.A0