



SPECIFICATIONS
 Current Rating: 2A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 500V AC/minute
 Material: Nylon 66+GF,UL94V-0
 Color: Natural(Black)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
F2544H-02P-A	2.54	5.08
F2544H-03P-A	5.08	7.62
F2544H-04P-A	7.62	10.16
F2544H-05P-A	10.16	12.70
F2544H-06P-A	12.70	15.24
F2544H-07P-A	15.24	17.78
F2544H-08P-A	17.78	20.32
F2544H-09P-A	20.32	22.86
F2544H-10P-A	22.86	25.40
F2544H-11P-A	25.40	27.94
F2544H-12P-A	27.94	30.48
F2544H-13P-A	30.48	33.02
F2544H-14P-A	33.02	35.56
F2544H-15P-A	35.56	38.10
F2544H-16P-A	38.10	40.64
F2544H-17P-A	40.64	43.18
F2544H-18P-A	43.18	45.72
F2544H-19P-A	45.72	48.26
F2544H-20P-A	48.26	50.80
F2544H-21P-A	50.80	53.34
F2544H-22P-A	53.34	55.88
F2544H-23P-A	55.88	58.42
F2544H-24P-A	58.42	60.96
F2544H-25P-A	60.96	63.50

Allconnectors www.allconnectors.eu info@allconnectors.eu Tel: +49 (0)711 / 358 110 20 Fax: +49 (0)711 / 358 110 25			
UNIT	SCALE	SHEET	TITLE:
mm		1 of 1	
DRAWN BY	APPROVED BY		2.54mm PITCH HOUSING, FFC CONNECTOR, A TYPE
2004. 11. 06	2004. 11. 06		
GENERAL TOLERANCE			
B2	EN0911050541	2009. 11. 05	DRAW NO. : F2544H-XP-A
B1	REVISE	2007. 11. 30	
B0	NEW RELEASE	2005. 12. 05	
REV.	DESCRIPTION	DATE	
X. XX±0. 15			ANGLE±
X. XXX±0. 05			⊕
			REV. B2