

- * Poles:4-50
 - * Material:PBTP UL94V-0 BLACK
 - * Suitable CT2542 series terminal
 - * Mates with CW330 series Header
- Specifications**
- * Current rating: 3A AC, DC
 - * Voltage rating: 250V AC, DC
 - * Temperature range: -25°C~+85°C
 - * Insulation resistance: 1,000M Ω min.
 - * Withstand voltage: 1,000V AC/minute

CIRCUITS	PART NO.	DIMENSION		CIRCUITS	PART NO.	DIMENSION	
		A	B			A	B
4	PVF-H-2X02	0.100(2.54)	0.200(5.08)	28	PVF-H-2X14	1.300(33.02)	1.400(35.54)
6	PVF-H-2X03	0.200(5.08)	0.300(7.62)	30	PVF-H-2X15	1.400(35.54)	1.500(38.10)
8	PVF-H-2X04	0.300(7.62)	0.400(10.16)	32	PVF-H-2X16	1.500(38.10)	1.600(40.64)
10	PVF-H-2X05	0.400(10.16)	0.500(12.70)	34	PVF-H-2X17	1.600(40.64)	1.700(43.18)
12	PVF-H-2X06	0.500(12.70)	0.600(15.24)	36	PVF-H-2X18	1.700(43.18)	1.800(45.72)
14	PVF-H-2X07	0.600(15.24)	0.700(17.78)	38	PVF-H-2X19	1.800(45.72)	1.900(48.26)
16	PVF-H-2X08	0.700(17.78)	0.800(20.32)	40	PVF-H-2X20	1.900(48.26)	2.000(50.80)
18	PVF-H-2X09	0.800(20.32)	0.900(22.86)	42	PVF-H-2X21	2.000(50.80)	2.100(53.34)
20	PVF-H-2X10	0.900(22.86)	1.000(25.40)	44	PVF-H-2X22	2.100(53.34)	2.200(55.88)
22	PVF-H-2X11	1.000(25.40)	1.100(27.94)	46	PVF-H-2X23	2.200(55.88)	2.300(58.42)
24	PVF-H-2X12	1.100(27.94)	1.200(30.48)	48	PVF-H-2X24	2.300(58.42)	2.400(60.96)
26	PVF-H-2X13	1.200(30.48)	1.300(33.02)	50	PVF-H-2X25	2.400(60.96)	2.500(63.50)

All Connectors

www.allconnectors.eu | info@allconnectors.eu
Tel. +49 (0)711 / 358 110 20 | Fax +49 (0)711 / 358 110 25

PART NO. PVF-H-2Xxx

DWG NO. PVF-H-2Xxx

FILE NO. HF2545-2X5


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIPTION: (2.54mm) pitch FFC/FPC connectors

AREA

REVISIONS

HK

DATE