

314A-XX B A A-R
1 2 3 4 5

- 1.Pin count
- XX: 05 to 56 pin
- 2.Contact
- B: Bottom contact
- 3.Plating
- A: G/F
- 4.Package
- A: Reel
- 5.RoHS

RECOMMENDED P.C. BOARD PATTERN LAYOUT
RECOMMENDED METAL MASK THICKNESS: T=0.15

- NOTES:
1. UNLESS OTHERWISE SPECIFIED, ALL TOLERANCES FOLLOW DRAWING COMMON STANDARD.
 2. MATERIAL OF COMPONENTS :
INSULATORLCP SERIES
SPACERNYLON SERIES
CONTACTPHOSPHOR BRONZE C5191R-H
HOLD DOWNBRASS C2680R-H
 3. GOLD FLASH & OVER NICKEL 50~150 u" UNDER-PLATING.

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±5°
0.	±
.0	±0.25
.00	±0.20

Allconnectors
www.allconnectors.eu | info@allconnectors.eu
Tel. +49 (0)711 / 358 110 20 | Fax +49 (0)711 / 358 110 25

SCALE: AS SHOWN	UNIT: mm
DRAWN Willis	2007/11/16
CHECKED / /	
APPROVED / /	

DRAWN NAME:
FPC Connector Horizontal type
Pitch 0.5mm ,Thickness 2.0 mm

PRODUCT NO. 314A-XXBAA-R


FILE NAME: 314A-XXBAA-R

REV.	DESCRIPTION	DATE	SIZE	REV.
1			A4	


POS.	DIM.A	DIM.B	DIM.C	DIM.D
5	7.25	6.80	2.00	3.00
6	7.75	7.30	2.50	3.50
7	8.25	7.80	3.00	4.00
8	8.75	8.30	3.50	4.50
9	9.25	8.80	4.00	5.00
10	9.75	9.30	4.50	5.50
11	10.25	9.80	5.00	6.00
12	10.75	10.30	5.50	6.50
13	11.25	10.80	6.00	7.00
14	11.75	11.30	6.50	7.50
15	12.25	11.80	7.00	8.00
16	12.75	12.30	7.50	8.50
17	13.25	12.80	8.00	9.00
18	13.75	13.30	8.50	9.50
19	14.25	13.80	9.00	10.00
20	14.75	14.30	9.50	10.50
21	15.25	14.80	10.00	11.00
22	15.75	15.30	10.50	11.50
23	16.25	15.80	11.00	12.00
24	16.75	16.30	11.50	12.50
25	17.25	16.80	12.00	13.00
26	17.75	17.30	12.50	13.50
27	18.25	17.80	13.00	14.00

POS.	DIM.A	DIM.B	DIM.C	DIM.D
28	18.75	18.30	13.50	14.50
29	19.25	18.80	14.00	15.00
30	19.75	19.30	14.50	15.50
31	20.25	19.80	15.00	16.00
32	20.75	20.30	15.50	16.50
33	21.25	20.80	16.00	17.00
34	21.75	21.30	16.50	17.50
35	22.25	21.80	17.00	18.00
36	22.75	22.30	17.50	18.50
37	23.25	22.80	18.00	19.00
38	23.75	23.30	18.50	19.50
39	24.25	23.80	19.00	20.00
40	24.75	24.30	19.50	20.50
41	25.25	24.80	20.00	21.00
42	25.75	25.30	20.50	21.50
43	26.25	25.80	21.00	22.00
44	26.75	26.30	21.50	22.50
45	27.25	26.80	22.00	23.00
46	27.75	27.30	22.50	23.50
47	28.25	27.80	23.00	24.00
48	28.75	28.30	23.50	24.50
49	29.25	28.80	24.00	25.00
50	29.75	29.30	24.50	25.50

POS.	DIM.A	DIM.B	DIM.C	DIM.D
51	30.25	29.80	25.00	26.00
52	30.75	30.30	25.50	26.50
53	31.25	30.80	26.00	27.00
54	31.75	31.30	26.50	27.50
55	32.25	31.80	27.00	28.00
56	32.75	32.30	27.50	28.50

UNLESS OTHERWISE SPECIFIED TOLERANCE		 <small>www.allconnectors.eu info@allconnectors.eu Tel. +49 (0)711 / 358 110 20 Fax +49 (0)711 / 358 110 25</small>
ANG.	±5°	
0.	±	
.0	±0.25	
.00	±0.20	
SCALE:	AS SHOWN	UNIT: mm
DRAWN	Willis	2007/11/16
CHECKED		/ /
APPROVED		/ /
REV.		
DRAWN NAME:		FPC Connector Horizontal type
		Pitch 0.5mm ,Thickness 2.0 mm
PRODUCT NO.		314A-XXBAA-R
FILE NAME:		314A-XXBAA-R

REV.	DESCRIPTION	DATE
1		
2		
3		
4		
5		
6		
7		

	SIZE	A4
---	------	----