

REV.	ECN.NO.	MODIFY.CONTENT	DATE
A			







NOTES:

1. Material:

- 1.1 Insulator: Thermo plastic (UL94V-0)
- 1.2 Actuator: Thermo plastic (UL94V-0)
- 1.3 Terminal: Phosphor Bronze
- 1.4 ME: Brass

2. Plating:

- 2.1 Terminal Matte Tin Or Gold Flash Plating Nickel Overall
- 2.2 ME Tin Plating Over Nickel.



Applicable FPC

RECOMMEND PCB LAYOUT TOLERANCE:±0.05

PIN NO	DIM. A	DIM. B	DIM. C	DIM. D	PIN NO.	DIM. A	DIM. B	DIM. C	DIM. D
04	3.77	1.50	2.60	3.27	23	13.27	11.50	12.10	12.77
05	4.27	2.00	3.10	3.77	24	13.77	11.50	12.60	13.27
06	4.77	2.50	3.60	4.27	25	14.27	12.00	13.10	13.77
07	5.27	3.00	4.10	4.77	26	14.77	12.50	13.60	14.27
08	5.77	3.50	4.60	5.27	27	15.27	13.00	14.10	14.77
09	6.27	4.00	5.10	5.77	28	15.77	13.50	14.60	15.27
10	6.77	4.50	5.60	6.27	29	16.27	14.00	15.10	15.77
11	7.27	5.00	6.10	6.77	30	16.77	14.50	15.60	16.27
12	7.77	5.50	6.60	7.27	31	17.27	15.00	16.10	16.77
13	8.27	6.00	7.10	7.77	32	17.77	15.50	16.60	17.27
14	8.77	6.50	7.60	8.27	33	18.27	16.00	17.10	17.77
15	9.27	7.00	8.10	8.77	34	18.77	16.50	17.60	18.27
16	9.77	7.50	8.60	9.27	35	19.27	17.00	18.10	18.77
17	10.27	8.00	9.10	9.77	36	19.77	17.50	18.60	19.27
18	10.77	8.50	9.60	10.27	37	20.27	18.00	19.10	19.77
19	11.27	9.00	10.10	10.77	38	20.77	18.50	19.60	20.27
20	11.77	9.50	10.60	11.27	39	21.27	19.00	20.10	20.77
21	12.27	10.00	11.10	11.77	40	21.77	19.50	20.60	21.27
22	12.77	10.50	11.60	12.27	n	n*0.5+1.77	(n-1)*0.5	n*0.5+0.6	n*0.5+1.27

GENERAL TOLERANCE		DRAWN	xiaohu.leng	09.17-12	SCALE	PART NO.	0.5PITCH 超薄型翻盖式
X. ±0.30	x.'± 1'	CHECKED	qlong.zhong	09.17-12	1/1	TITLE	0.5 Pitch FPC Connector HI.0
X.X ±0.25	.x '±0.1'	APPROVED	yewen.xie	09.17-12	UNITS	mm	成品SPEC图
X.XX ±0.20		File NO.					
X.XXX±0.10		REV.					
SHEET	1/1	Q'TY	1	A			