


PC BOARD LAYOUT:  
COMPONENT SIDE

NOTE:

- 1.MATERIAL:
- INSULATOR: NYLON (UL 94V-0)
- COVER: P.P.A.
- TERMINAL: PHOSPHOR BRONZE



FFC/FPC DIMENSION  
THICKNESS: 0.3mm  
TOLERANCE: 0.05mm

30	29.00	31.20	35.00
29	28.00	30.20	34.00
28	27.00	29.20	33.00
27	26.00	28.20	32.00
26	25.00	27.20	31.00
25	24.00	26.20	30.00
24	23.00	25.20	29.00
23	22.00	24.20	28.00
22	21.00	23.20	27.00
21	20.00	22.20	26.00
20	19.00	21.20	25.00
19	18.00	20.20	24.00
18	17.00	19.20	23.00
17	16.00	18.20	22.00
16	15.00	17.20	21.00
15	14.00	16.20	20.00
14	13.00	15.20	19.00
13	12.00	14.20	18.00
12	11.00	13.20	17.00
11	10.00	12.20	16.00
10	9.00	11.20	15.00
9	8.00	10.20	14.00
8	7.00	9.20	13.00
7	6.00	8.20	12.00
6	5.00	7.20	11.00
5	4.00	6.20	10.00
4	3.00	5.20	9.00
3	2.00	4.20	8.00
CKT	DIM A	DIM B	DIM C

**All Connectors**

www.allconnectors.de  
Tel.: 0049 711 7009503  
70794 Filderstadt - Germany

info@allconnectors.de  
Fax: 0049 711 7009504  
Kettnerstr. 25


**RoHS Compliant**

DRAWING BY CY  
CHECKED BY GENIUS  
UNIT/mm SCALE 1:1  
DATE  
SIZE A4

TOLERANCES ARE

X ±  
X ± 0.20  
.XX ± 0.10  
.XXX ±  
ANG ±

PJECTION



ORDER INFORMATION

FPA-DZAL60-xx-LF  
SERIES DIP 180° LEADFREE 03~30WAY HIGH 6.0mm ZIF L TYPE FOOT POSITION SINGLE CONTACT

DESCRIPTION: 1.00mm, ZIF FFC/FPC CONN. ASS'Y(DIP)