



- NOTES:
- 1:Material:
 - 1.1 Housing: Thermoplastic UL94V-0 color:black.
 - 1.2 Contact:Phosphor bronze T=0.30mm.
 - 1.3 Shell: Copper alloy T=0.40mm.
 - 2:Specification:
 - 2.1 Current rating: 0.5 A Max.
 - 2.2 Voltage rating: 40 V ac(rms) Max.
 - 2.3 Contact resistance: 50 mW Max.
 - 2.4 Dielectric withstanding
voltage: 100 V(ac) for 1 min.
 - 2.5 Insulation resistance:1000 MW Min.
 - 2.6 Operation temperature range:-25°C~85°C

All Connectors

www.allconnectors.de
Tel.: 0049 711 7009503
70794-Filderstadt Germany

Info@allconnectors.de
Fax: 0049 711 7009504
Kettnerstr. 25

RoHS Compliant

DRAWING BY CY
CHECKED BY GENIUS
UNIT / mm SCALE 1 : 1
DATE
SIZE A4

TOLERANCES ARE

X ±
X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION



ORDER INFORMATION

HDMI-PS-19-LF
SERIES | | LEADFREE
19 WAY
SOLDER
MALE

DESCRIPTION: HDMI-19P SOLDER