

Note:

Specification:

1. Current rating: 0.5 A Max.
2. Dielectric withstanding voltage: 30 V(ac) for 1 minute.
3. Contact resistance: 30 mΩ Max.
4. Insulation resistance: 1000 MΩ Min at DC 500V.
5. Insertion force: 4.5 Kgf Max.
6. Extraction force: 1.0 Kgf Min.
7. Temperature range: -55°C~+105°C

4	Spacer	1	LCP		Black
3	Shell	1	Brass		80U"min Nickel Plated
2	Contact	19	COPPER ALLOY		Contact area:0.8u"min Gold Plated over 40u"Nickel min. Solder area:80u"min Tin Plated over 40u"Nickel min. (All Gold)
1	Housing	1	LCP		Black
No.	Name	Q'ty	Material	Remarks&Thickness	Finish

RoHS Compliant

All Connectors

www.allconnectors.de
Tel.: 0049 711 7009503
70794 Filderstadt - Germany

info@allconnectors.de
Fax: 0049 711 7009504
Kettnerstr. 25

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1


DATE

SIZE A4

TOLERANCES ARE

X ±
X ± 0.20
.XX ± 0.10
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

HDMI-SDZB-19-LF
SERIES | | | | | LEADFREE
19WAY
B TYPE
CLIP
DIP 180°
FEMALE

DESCRIPTION: HDMI-19PIN(F) 180°DIP