



NOTE:

1. MATERIAL:
 - 1-1. HOUSING: LCP.
 - 1-2. CONTACT: BRONZE.
 - 1-3. SHELL: BRASS.
2. PLATING:
 - 2-1. CONTACT: CONTACT AREA SEE TABLE A/SOLDER AREA GOLD FLASH. UNDER NICKEL 50u" MIN.
 - 2-2. SHELL: NICKEL 60u" MIN.
3. SAFETY:
 - 3-1. CONTACT RESISTANCE: CONTACT 30mohm MAX. SHELL 50mohm MAX.
 - 3-2. INSULATION RESISTANCE: UNMATED 100Mohm MIN. MATED 10Mohm MIN.
 - 3-3. DIELECTRIC STRENGTH: 500 Vac MIN.
 - 3-4. CURRENT RATING: 0.5A MIN.

BOM	
19	CONTACT
E1	SHELL
1	HOUSING
数量	零件

RoHS Compliant



www.allconnectors.co Inc@allconnectors.co
 Tel: 049 711 70800 Fax: 049 711 70804
 1764 Ridsdale Gateway Katoomba, N.S.W.

DRAWING BY CY		TOLERANCES ARE X± X± XX± XXX± ANG±
CHECKED BY GENIUS		
UNIT /mm	SCALE 1:1	
DATE		
SIZE A4	PROJECTION 	



ORDER INFORMATION

MHDMI-SWP-19-LF

SERIES FEMALE 90°SMT 19WAY LEADFREE
 WITH LOCATING PEG

DESCRIPTION: HDMI 19P (F) Dip