

0.75mm .030" Center Wire to Board Connector

0750 Series

■ PLUG HOUSING

Part No.: 0750-HS-xxP

Specifications



Electrical

Voltage Rating: 50V(AC/DC)
 Current Rating: 0.5A AC/DC Per Pin
 Withstanding Voltage: 500V AC/minute
 Insulation Resistance: 100M Ω Min
 Contact Resistance: 20m Ω Max
 Accepts terminal: 0750-Q-P
 0750-T-T-S

Mates with: 0750-SMTR-xxP

Material

Circuits: 30
 Housing: Thermal Plastic, UL 94V-0
 Shield: Copper Alloy, Tin plated
 Temperature Range: -25--+85°C



Ordering Information and Dimensions

CIRCUITS	PART NO.	DIMENSION		
		A	B	C
30	0750-HS-30P	27.50	23.60	21.75

0750 Series


■ TERMINAL

Part No.: 0750-Q-P

0750-T-T-S

Material

Terminal: Copper Alloy
 Thickness: 0.1mm
 Plating: Gold plated, Tin plated
 Applicable Wire: AWG#32-AWG#36
 Insulation O.D.: 0.25mm(AWG#36)
 0.38mm(AWG#32)
 QTY: 20,000 pcs/ reel
 Accepts housing: 0750-HS-xxP



SECTION A-A



SECTION B-B

