



■ SPECIFICATIONS

- Voltage rating: 100V AC, DC
- Current rating: 1A, AC, DC
- Withstanding Voltage: 500V AC/minute
- Insulation resistance: 500MΩmin
- Temperature range: -25° C~+85° C
- Contact resistance: Intial value/10mΩmax
- After enviornmental testing/20mΩmax

■ HOUSING

- Part No.: 0800-XX
- Poles: 2-20
- Material: Polgamide UL 94V-0
- Q'ty: 1000pcs/bag

Poles	Part No	Dimensions (mm)	
		A	B
2	0800-02	0.80	2.40
3	0800-03	1.60	3.20
4	0800-04	2.40	4.80
5	0800-05	3.20	4.80
6	0800-06	4.00	5.60
7	0800-07	4.80	6.40
8	0800-08	5.60	7.20
9	0800-09	6.40	8.00
10	0800-10	7.20	8.80
11	0800-11	8.00	9.60
12	0800-12	8.80	10.40
13	0800-13	9.60	11.20
14	0800-14	10.40	12.00
15	0800-15	11.20	12.80
16	0800-16	12.00	13.60
17	0800-17	12.80	14.40
18	0800-18	13.60	15.20
19	0800-19	14.40	16.00
20	0800-20	15.20	16.80

Allconnectors

www.allconnectors.eu | info@allconnectors.eu
Tel. +49 (0)711 / 358 110 20 | Fax +49 (0)711 / 358 110 25

APPROVED BY	DATE	SCALE	TOLERANCE	
	2007/04/20	4:1	.0	±0.3
CHECKED BY	UNIT	VIEW	.00	±0.2
董坤	mm	⊕ □	.000	±0.1
DRAWN BY	VER NO.	SIZE	.0	±
	D1	A4	.0	±

PART NO 0800-XX

0.8mm Crimp Style connectors