



## ■ SPECIFICATIONS

- Voltage rating: 30V AC, DC
- Current rating: 0.5A, AC, DC
- Withstanding Voltage: 200V AC/minute
- Insulation resistance: 100MΩmin
- Temperature range: -25° C ~ +85° C
- Contact resistance: Initial value/20mΩmax
- After environmental testing/20mΩmax

## ■ HOUSING

- Part No.: 0800E/EG-XX
- Poles: 2-24
- Material: Nylon 46, UL94V-0
- Mates with SWB 0801 0802 series wafer
- Q'ty: 1000pcs/bag

Poles	PART NO.	Dimensions (mm)			
		A	B	C	D
2	0800E-02	0.80	1.78	2.40	3.20
3	0800E-03	1.60	2.58	3.20	4.00
4	0800E-04	2.40	3.38	4.00	4.80
5	0800E-05	3.20	4.18	4.80	5.60
6	0800E-06	4.00	4.98	5.60	6.40
7	0800E-07	4.80	5.78	6.40	7.20
8	0800E-08	5.60	6.58	7.20	8.00
9	0800E-09	6.40	7.38	8.00	8.80
10	0800E-10	7.20	8.18	8.80	9.60
11	0800E-11	8.00	8.98	9.60	10.40
12	0800E-12	8.80	9.78	10.40	11.20
13	0800E-13	9.60	10.58	11.20	12.00
14	0800E-14	10.40	11.38	12.00	12.80
15	0800E-15	11.20	12.18	12.80	13.60
16	0800E-16	12.00	12.98	13.60	14.40
17	0800E-17	12.80	13.78	14.40	15.20
18	0800E-18	13.60	14.58	15.20	16.00
19	0800E-19	14.40	15.38	16.00	16.80
20	0800E-20	15.20	16.18	16.80	17.60
21	0800E-21	16.00	16.98	17.60	18.40
22	0800E-22	16.80	17.78	18.40	19.20
23	0800E-23	17.60	18.58	19.20	20.00
24	0800E-24	18.40	19.38	20.00	20.80

**Allconnectors**

www.allconnectors.eu | info@allconnectors.eu  
Tel. +49 (0)711 / 358 110 20 | Fax +49 (0)711 / 358 110 25

Date	Old VER NO.	New VER NO.	Modify the content	Remark
2010/06/22	A	B		

PART NO 0800E-XX/0800EG-XX  
0.8mm Crimp Style connectors

UNIT	VIEW	SIZE	TOLERANCE	
mm		A4	.0	±0.3
			.00	±0.2
SCALE	DRAWN DATA	VER NO.	.000	±0.1
4:1	2007/05/03	B		

DRAWN BY CHECKED BY APPROVED BY