



Recommend PCB Layout

■ SPECIFICATIONS

- Voltage rating: 100V AC, DC
- Current rating: 1A, AC, DC
- Withstanding Voltage: 500V AC/minute
- Insulation resistance: 500MΩmin
- Temperature range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- Contact resistance: Initial value/10mΩmax
- After enviornmental testing/20mΩmax

■ WAFER

- Part No.: 0801-XX
- Poles: 2-20
- Material: Polgamide UL 94V-0
- Q'ty: 1000pcs/bag

Poles	Part No	Dimensions (mm)	
		A	B
2	0801-02	0.80	3.80
3	0801-03	1.60	4.60
4	0801-04	2.40	5.40
5	0801-05	3.20	6.20
6	0801-06	4.00	7.00
7	0801-07	4.80	7.80
8	0801-08	5.60	8.60
9	0801-09	6.40	9.40
10	0801-10	7.20	10.20
11	0801-11	8.00	11.00
12	0801-12	8.80	11.80
13	0801-13	9.60	12.60
14	0801-14	10.40	13.40
15	0801-15	11.20	14.20
16	0802-16	12.00	15.00
17	0802-17	12.80	15.80
18	0802-18	13.60	16.60
19	0802-19	14.40	17.40
20	0802-20	15.20	18.20

Allconnectors
 www.allconnectors.eu | info@allconnectors.eu
 Tel. +49 (0)711 / 358 110 20 | Fax +49 (0)711 / 358 110 25

APPROVED BY	DATE	SCALE	TOLERANCE	
	2007/04/20	4:1	.0	±0.3
CHECKED BY	UNIT	VIEW	.00	±0.2
	mm	⊕ □	.000	±0.1
DRAWN BY	VER NO.	SIZE	.0	±
	D1	A4	.0	±

PART NO 0801-XX

0.8mm Crimp Style connectors