



NOTES:

1. MATERIALS:

HOUSING :Nylon, UL 94V-0.
 CONTACT :Phosphor Bronze, T=0.15mm.
 PLATING :NICKET BASE 50 μ " OVER MATERIAL
 PLATING :Selective Gold.

2. SPECIFICATION:

CURRENT :AWG #28 :1A ;AWG #30 :0.5A
 AWG#32 :0.3A

CONTACT RESISTANCE:50MW MAX.

INSULATION RESISTANCE:500MW MIN.

DIELECTIC WITHSTANDING VOLTAGE:100V AC.

APPLICABLE WIRE SIZE :Standard #28 to #32 AWG.

ACCEPTS:CNT235-XXH SERIES HOUSING.

Allconnectors

www.allconnectors.eu | info@allconnectors.eu
 Tel. +49 (0)711 / 358 110 20 | Fax +49 (0)711 / 358 110 25

PART NO. DF19-T-28

DWG NO. DF19-T-28

FILE NO.

UNIT / mm

SCALE 1:1

APPROVED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

X.
 XX.
 XXX.
 AWG

DESCRIP TION:

DF19 1.0mm Single Rowocket
 (Terminal)

AREA

REVISIONS

HK

DATE