



**SPECIFICATIONS**

Current Rating : 1A AC,DC  
 Voltage Rating : 100V AC,DC  
 Temperature Range : -25°C~+85°C  
 Contact Resistance : 20mΩ Max.  
 Insulation Resistance : 500MΩ Min.  
 Withstanding Voltage : 500V AC/Min.  
 Pin Material : Phosphor Bronze/Tin-plated  
 Solder Tabs : Brass/Tin-plated  
 Material : Nylon 6T, UL94V-0

DF13-WPx-1Xxx-LF  
 LEADFREE  
 G:GOLD PLATED  
 BLANK:TIN PLATED

**RoHS Compliant**

Ordering Information & Dimensions

PART NO.	Dimensions		
	A	B	C
DF13-WP-1X02	1.25	4.15	5.65
DF13-WP-1X03	2.50	5.40	6.90
DF13-WP-1X04	3.75	6.65	8.15
DF13-WP-1X05	5.00	7.90	9.40
DF13-WP-1X06	6.25	9.15	10.65
DF13-WP-1X07	7.50	10.40	11.90
DF13-WP-1X08	8.75	11.65	13.15
DF13-WP-1X09	10.00	12.90	14.40
DF13-WP-1X10	11.25	14.15	15.65
DF13-WP-1X11	12.50	15.40	16.90
DF13-WP-1X12	13.75	16.65	18.15
DF13-WP-1X13	16.25	19.15	20.65
DF13-WP-1X14	17.50	20.40	21.90

PART NO. DF13-WPx-1Xxx		CHECKED BY CY		TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIP TION: 1.25mm Wire-to-Board Header SMD 90° TYPE		
DWG NO. DF13-WPx-1Xxx		DRAWING BY					
FILE NO.		PROJECTION		AREA	REVISIONS	HK	DATE
UNIT / mm	SCALE 1 : 1						