



SPECIFICATIONS

Electrical

- Current Rating: 1A AC, DC
- Voltage Rating: 150V AC/ max.
- Operating Temp.: -25°C ~ +85°C
- Insulation Resistance: 500MΩ/ min.
- Withstand Voltage: 500V AC/ min.
- Contact Resistance: 30MΩ/ max.

Material

- Terminal Material: Brass/ Tin-plated
- Material: Nylon 6T, UL94V-0

Poles	Dimension mm (in.)		Part No.
	A	B	
2	1.25 (0.049)	7.50 (0.295)	DF14-WX-02
4	3.75 (0.147)	10.00 (0.394)	DF14-WX-04
12	13.75 (0.541)	20.00 (0.787)	DF14-WX-12
20	23.75 (0.935)	30.00 (1.181)	DF14-WX-20
30	36.25 (1.427)	42.50 (1.673)	DF14-WX-30

PART NO. DF14-WX-XX

DWG NO. DF14-WX-XX

FILE NO.

UNIT / mm

SCALE 1:1

APPROVED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X
.XX
.XXX
AWG

DESCRIPTION:

AREA	REVISIONS	HK	DATE
------	-----------	----	------