



SEC:A-A

Specification

Pitch Between Ploes: 1.27mm
 Current Rating: 1.5A AC/DC
 Contact Resistance: 30mΩ MAX.
 Insulation Resistance: 1,000MΩ MIN.
 Withstand Voltage: 500V AC/Minute

Features

Available Number of Circuits: 07
 Material: Nylon 66 UL 94V-0

TU1271HNO-07K- *-NL

G3AE: Gold 3 μ" & Tin-plated
 G15AE: Gold 15 μ" & Tin-plated

Allconnectors

www.allconnectors.de
 Tel.: 0049 711 7009503
 70794 Filderstadt - Germany

info@allconnectors.de
 Fax: 0049 711 7009504
 Kettenerstr. 25

UNIT: mm

GENERAL TOLERANCE

ANGLE

±5°

DIM:

X.X ±0.25
 X.XX ±0.15
 X.XXX ±0.08

SCALE: 1 : 1

SHEET: 1 OF 1

DRAWN: *Hu2in*

CHECKED: *Wayne*

| REV | REVISION RECORD | DATE |
|-----|-----------------|------------|
| B/0 | 更換版本 | 2008-07-15 |
| | | |
| | | |
| | | |
| | | |

| | | |
|---|------|---|
| 6 | SIZE | DESCRIPTION: 1.27mm PITCH WIRE TO BOARD CONNECTOR HOUSING |
| | A4 | PART NO: TU1271HNO-07K- *-NL |