



Specification

Pitch Between Ploes: 1.27mm
 Current Rating: 1.5A AC/DC
 Contact Resistance: 30mΩ MAX.
 Insulation Resistance: 1,000MΩ MIN.
 Withstand Voltage: 500V AC/Minute

Features

Available Number of Circuits: 07
 Material: Nylon 66 UL 94V-0

TU1271HNO-07K-*

G3AE: Gold 3U" & Tin-plated
 G15AE: Gold 15U" & Tin-plated

Allconnectors

www.allconnectors.de
 Tel.: 0049 711 7009503
 70794 Filderstadt - Germany

info@allconnectors.de
 Fax: 0049 711 7009504
 Kettnerstr. 25

UNIT: mm

GENERAL TOLERANCE

ANGLE

±5°

DIM:

X.X ±0.25
 X.XX ±0.15
 X.XXX ±0.08

SCALE: 1 : 1

SHEET: 1 OF 1

DRAWN: *Hu2in*

CHECKED: *Wayne*

REV	REVISION RECORD	DATE
A/0	NEW DRAWING	2008-05-05

6	SIZE	DESCRIPTION: 1.27mm PITCH WIRE TO BOARD CONNECTOR HOUSING
	A4	PART NO: TU1271HNO-07K-*