


Specification

Current Rating : 1A AC/DC
 Voltage Rating : 1,400V AC/DC
 Contact Resistance : 20mΩ MAX.
 Withstand Voltage : 3,800V AC/Minute
 Insulation Resistance : 1,000MΩ MIN.
 Temperature Range : -25° C To +85° C
 Applicable Wire : AWG #24To #28


BD-T-24-LF
 LEADFREE
 RoHS Compliant

Contact Information


Part No.	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
BD-T-24	AWG #24-#28	1.70mm MAX.	Phosphor bronze	See note	10,000 pcs



SEC:A-A



SEC:B-B



SEC:C-C

Allconnectors
 www.allconnectors.eu | info@allconnectors.eu
 Tel. +49 (0)711 / 358 110 20 | Fax +49 (0)711 / 358 110 25

PART NO. BD-T-24

DWG NO. BD-T-24

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2

.XX ±

.XXX ±

AWG

DESCRIPTION:

3.50mm PITCH WIRE TO BOARD
 CRIMP TERMINAL

AREA

REVISIONS

HK

DATE