



SPECIFICATIONS

Current Rating: 3A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 30m ohm Min.  
 Insulation Resistance: 1000 M OHM Min.  
 Withstanding Voltage: 650V AC/minute  
 Material: Nylon 66,UL94V-0  
 Color: Black

DF3-R-xx-LF  
 LEADFREE

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
DF3-R-02	2.00	6.00
DF3-R-03	4.00	8.00
DF3-R-04	6.00	10.00
DF3-R-05	8.00	12.00
DF3-R-06	10.00	14.00
DF3-R-07	12.00	16.00
DF3-R-08	14.00	18.00
DF3-R-09	16.00	20.00
DF3-R-10	18.00	22.00
DF3-R-11	20.00	24.00
DF3-R-12	22.00	26.00
DF3-R-13	24.00	28.00
DF3-R-14	26.00	30.00
DF3-R-15	28.00	32.00

RoHS Compliant

<p>www.allconnectors.eu   info@allconnectors.eu                  Tel. +49 (0)711 / 358 110 20   Fax +49 (0)711 / 358 110 25</p>	PART NO. DF3-R-xx		CHECKED BY CY	TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIP TION:		
	DWG NO. DF3-R-xx					DRAWING BY	
	UNIT / mm	SCALE 1:1	PROJECTION	AREA	REVISIONS	HK	DATE