



Dimensional & Ordering Information: $\triangle C$

Circuits	Part No.	Dimensions			Pcs/Bag
		A	B	C	
2	PA-DX-02	—	8.0	—	1000
3	PA-DX-03	4.00	10.0	—	1000
4	PA-DX-04	6.00	12.0	—	1000
5	PA-DX-05	8.00	14.0	7.00	1000
6	PA-DX-06	10.00	16.0		1000
7	PA-DX-07	12.00	18.0		500
8	PA-DX-08	14.00	20.0	13.60	500
9	PA-DX-09	16.00	22.0		500
10	PA-DX-10	18.00	24.0		500
11	PA-DX-11	20.00	26.0		500
12	PA-DX-12	22.00	28.0		250
13	PA-DX-13	24.00	30.0	250	
14	PA-DX-14	26.00	32.0	250	
15	PA-DX-15	28.00	34.0	250	

Material: *Insulator: Thermal Plasticity Resin UL 94V-0 (Milky Yellow)
 *Contact: Brass, Matte Tin Plated
 Note: RoHS and Halogen Free Compliance

PA-DX-xx-LF
 LEADFREE
 RoHS Compliant

 www.allconnectors.eu info@allconnectors.eu Tel. +49 (0)711 / 358 110 20 Fax +49 (0)711 / 358 110 25	PART NO. PA-DX-xx		CHECKED BY CY	TOLERANCES ARE .X ± .XX ± .XXX ± AWG	DESCRIP TION:	AREA	REVISIONS	HK	DATE
	DWG NO. PA-DX-xx								
UNIT / mm	SCALE 1:1	PROJECTION							