



**Features:**

- \* Available in 2 through 16 circuits
- \* Material: Insulator: Nylon 66 UL 94V-0

**Specifications:**

Rated Voltage	125V AC,DC
Rated Current	2A (AWG #24)
Withstand Voltage	1000V AC/minute
Contact Resistance	20mΩ (MAX.)
Insulation Resistance	1,000MΩ (MIN.)
Temperature Range	-25°~+95°C
Applicable P.C.B. Thickness	0.8~1.6mm
Applicable P.C.B. Hole dia.	$\phi 0.80 \pm 0.05$ mm

**Dimensional & Ordering Information:**

Circuits	Part No.	Dimensions			PCS/BAG
		A	B	C	
2	YH20-R-02	2.00	4.75	5.98	1000
3	YH20-R-03	4.00	6.75	7.98	
4	YH20-R-04	6.00	8.75	9.98	
5	YH20-R-05	8.00	10.75	11.98	
6	YH20-R-06	10.00	12.75	13.98	
7	YH20-R-07	12.00	14.75	15.98	
8	YH20-R-08	14.00	16.75	17.98	
9	YH20-R-09	16.00	18.75	19.98	
10	YH20-R-10	18.00	20.75	21.98	
11	YH20-R-11	20.00	22.75	23.98	
12	YH20-R-12	22.00	24.75	25.98	
13	YH20-R-13	24.00	26.75	27.98	
14	YH20-R-14	26.00	28.75	29.98	
15	YH20-R-15	28.00	30.75	31.98	
16	YH20-R-16	30.00	32.75	33.98	

PART NO. YH20-R-xx		APPROVED BY CY		TOLERANCES ARE .X .XX .XXX AWG		DESCRIP TION:				
DWG NO. YH20-R-xx		DRAWING BY								
FILE NO.		PROJECTION		AREA	REVISIONS	HK	DATE			
UNIT / mm	SCALE 1:1									