



SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 500MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Black

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
C2505HF-02P	2.50	5.50
C2505HF-03P	5.00	8.00
C2505HF-04P	7.50	10.50
C2505HF-05P	10.00	13.00
C2505HF-06P	12.50	15.50
C2505HF-07P	15.00	18.00
C2505HF-08P	17.50	20.50
C2505HF-09P	20.00	23.00
C2505HF-10P	22.50	25.50
C2505HF-11P	25.00	28.00
C2505HF-12P	27.50	30.50

All Connectors			
<small>www.allconnectors.eu info@allconnectors.eu Tel. +49 (0)711 / 358 110 20 Fax +49 (0)711 / 358 110 25</small>			
UNIT	SCALE	SHEET	TITLE:
mm		1 of 1	2.50mm PITCH HOUSING-RECEPTACLE
DRAWN BY	APPROVED BY		
2001.02.01	2001.02.01		
B2	ECN NO. EN0910160501	2009.10.16	GENERAL TOLERANCE
B1	REVISE	2005.11.24	X. X±0.25 ANGLE±
B0	NEW RELEASE	2005.10.17	X. XX±0.15
REV.	DESCRIPTION	DATE	X. XXX±0.05
DRAW NO. :			REV. B2
C2505HF-XP			