



SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 500MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Black

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
C2505HM-02P	2.50	8.00
C2505HM-03P	5.00	10.50
C2505HM-04P	7.50	13.00
C2505HM-05P	10.00	15.50
C2505HM-06P	12.50	18.00
C2505HM-07P	15.00	20.50
C2505HM-08P	17.50	23.00
C2505HM-09P	20.00	25.50
C2505HM-10P	22.50	28.00
C2505HM-11P	25.00	30.50
C2505HM-12P	27.50	33.00

All Connectors www.allconnectors.eu info@allconnectors.eu Tel: +49 (0)711 / 358 110 20 Fax: +49 (0)711 / 358 110 25				
UNIT	SCALE	SHEET	TITLE:	
mm		1 of 1	2.50mm PITCH HOUSING-PLUG	
DRAWN BY	APPROVED BY			
2001.02.01	2001.02.01			
GENERAL TOLERANCE				
B1	ECN NO. EN0910160501	2009.10.16	X. X±0.25	ANGLE±
B0	NEW RELEASE	2005.10.17	X. XX±0.15	
REV.	DESCRIPTION	DATE	X. XXX±0.05	DRW NO. : C2505HM-XP
				REV. B1