



■ 技术参数 (SPECIFICATIONS)

- ◆ 额定电压: 130V AC DC
Voltage rating: 130V AC DC
- ◆ 额定电流: 1.0A AC DC MIN
Current rating: 1.0A AC DC MIN
- ◆ 耐压值: 800V AC/minute
Withstand voltage: 800V AC/minute
- ◆ 绝缘电阻: 1000MΩ MIN
Insulation resistance: 1000MΩ MIN
- ◆ 接触电阻: 20mΩ MAX
Contact resistance: 20mΩ MAX
- ◆ 工作温度: -25°C ~ +85°C
Working Temperature: -25°C ~ +85°C
- ◆ 间距: 2.5 mm
Pitch: 2.5 mm

■ 材料 (MATERIAL)

- ◆ 端子: 磷青铜
Terminal: Phosphor Bronze

				<p>一般公差 GENERAL TOLERANCE</p> <p>. X ±0.3 . XX ±0.2 . XXX ±0.1</p>				<p>Allconnectors</p> <p>www.allconnectors.de info@allconnectors.de Tel.: 0049 711 7009503 Fax: 0049 711 7009504 70794 Filderstadt - Germany Kettenerstr. 25</p>				料号 PART NO C2510TF-XX			
								品名 TITLE 2.5mm Crimp Style connectors							
2011/06/30	A	B	修改图框格式				核准 APPD	审核 CHK	绘图 DR	日期 DATA					
日期 DATE	旧版次 OLD REV	新版次 NEW REV	变更内容 DESCRIPTION	审核 CHK	核准 APPD	角法 PROJECT	Rodney	兰雄	刘小菊	2010/11/10	单位 UNIT MM	比例 SCALE 1/1	图号 NUMBER LDZY-8120	版次 REV B	