



Specification

Material: Nylon 66 UL 94V-2

Poles	Dimension mm (in.)		Part No.
	A	B	
2	2.50 (0.098)	6.00 (0.236)	XH-H-02
3	5.00 (0.197)	8.50 (0.335)	XH-H-03
4	7.50 (0.295)	12.00 (0.472)	XH-H-04
5	10.00 (0.394)	13.50 (0.531)	XH-H-05
6	12.50 (0.492)	16.00 (0.630)	XH-H-06
7	15.00 (0.591)	18.50 (0.728)	XH-H-07
8	17.50 (0.689)	21.00 (0.827)	XH-H-08
9	20.00 (0.787)	23.50 (0.925)	XH-H-09
10	22.50 (0.886)	26.00 (1.024)	XH-H-10
11	25.00 (0.984)	28.50 (1.122)	XH-H-11
12	27.50 (1.802)	31.00 (1.220)	XH-H-12
13	30.00 (1.181)	33.50 (1.319)	XH-H-13
14	32.50 (1.280)	36.00 (1.417)	XH-H-14
15	35.00 (1.378)	38.50 (1.516)	XH-H-15
16	37.50 (1.476)	41.00 (1.614)	XH-H-16
17	40.00 (1.575)	43.50 (1.713)	XH-H-17
18	42.50 (1.673)	46.00 (1.811)	XH-H-18
19	45.00 (1.772)	48.50 (1.909)	XH-H-19
20	47.50 (1.870)	51.00 (2.008)	XH-H-20

PART NO. XH-H-xx

DWG NO. XH-H-xx

APPROVED BY CY

TOLERANCES ARE

FILE NO.

DRAWING BY

.X
.XX
.XXX
AWG

DESCRIPTION:

UNIT / mm

SCALE 1:1

PROJECTION

AREA

REVISIONS

HK

DATE

Allconnectors

www.allconnectors.eu | info@allconnectors.eu
Tel. +49 (0)711 / 358 110 20 | Fax +49 (0)711 / 358 110 25