


Specifications:
 Current Rating:3.0A AC,DC
 Voltage Rating:250V AC,DC
 Contact Resistance:20mohm Max
 Insulation Resistance:1000Mohm Min.
 Withstanding Voltage:1000V AC/minute
 Operating Temperature Range:-40°C~+105°C
 Material and Finish:
 Insulator:High Temp Plastic (Nylon 66 UL94V-0)
 Insulator Color:Black
 Contact:Brass
 Plating:Gold & Tin Plated

Dimension:

Circuits	Dimension:		Circuits	Dimension:	
	A	B		A	B
02	2.54	5.08	12	27.94	30.48
03	5.08	7.62	13	30.48	33.02
04	7.62	10.16	14	33.02	35.56
05	10.16	12.70	15	35.56	38.10
06	12.70	15.24	16	38.10	40.64
07	15.24	17.78	17	40.64	43.18
08	17.78	20.32	18	43.18	45.72
09	20.32	22.86	19	45.72	48.26
10	22.86	25.40	20	48.26	50.80
11	25.40	27.94			



P.C.B. Layout

www.allconnectors.de
 Tel.: 0049 711 7009503
 70794 Filderstadt - Germany

info@allconnectors.de
 Fax: 0049 711 7009504
 Kettenerstr. 25

RoHS Compliant

DRAWING BY CY
 CHECKED BY GENIUS

UNIT/ mm SCALE 1 : 1

DATE _____

SIZE A4 PROJECTION

TOLERANCES ARE

X. ±
 X ± 0.20
 .XX ± 0.15
 .XXX ±
 ANG ±

ORDER INFORMATION

HE 14-Rx-1Xxx-LF

SERIES

DIP 90°

LEADFREE

1X02:02WAY

1X20:20WAY

T:TIN PLATED

G:GOLD PLATED

DESCRIPTION:2.54mm Wire to Board Wafer Single Row R/A Type