



■ SPECIFICATIONS

- Voltage Rating : 250 V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1,000V AC/minute
- Insulation Resistance : 1,000M Ω min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20m Ω max

■ HOUSING

- Part No. : JS-1142A-XX
- Poles : 2 - 18
- Material : PBT UL94V-0
- Q' ty : 1,000 pcs./Bag

Poles	Part No.	Dimensions(mm)		
		A	B	C
2	JS-1142A-02	2.54	5.08	-----
3	JS-1142A-03	5.08	7.62	-----
4	JS-1142A-04	7.62	10.16	5.08
5	JS-1142A-05	10.16	12.70	7.62
6	JS-1142A-06	12.70	15.24	10.16
7	JS-1142A-07	15.24	17.78	12.70
8	JS-1142A-08	17.78	20.32	15.24
9	JS-1142A-09	20.32	22.86	17.78
10	JS-1142A-10	22.86	25.40	20.32
11	JS-1142A-11	25.40	27.94	22.86
12	JS-1142A-12	27.94	30.48	25.40
13	JS-1142A-13	30.48	33.02	27.94
14	JS-1142A-14	33.02	35.56	30.48
15	JS-1142A-15	35.56	38.10	33.02
16	JS-1142A-16	38.10	40.64	35.56
17	JS-1142A-17	40.64	43.18	38.10
18	JS-1142A-18	43.18	45.72	40.64

All Connectors

www.allconnectors.de
 Tel.: 0049 711 7009503
 70794 Filderstadt - Germany

Info@allconnectors.de
 Fax: 0049 711 7009504
 Kettelerstr. 25

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	DATE	LTR	REVISION RECORD	DATE
林陳鏞	1:1	mm	.0 ±0.3	ECR	RoHS Compliant	06/04/01			
CHECKED BY	PROJ	VER NO.	.00 ±0.2	ECR	200705-019	07/05/28			
			.000 ±0.1	ECR	200809-009	08/09/10			
PART NO	JS-1142A-XX	α3	ALL ±				CUSTOMER		
2.54mm Crimp Style Connectors Housing	黃科源	A4	ANGLE				Conforms to The RoHS Instruction		
	2008/09/10		0° ±						
			.0° ±						