



#### ■ SPECIFICATIONS

- Voltage Rating : 250 V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1,000V AC/minute
- Insulation Resistance : 1,000M  $\Omega$  min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20m  $\Omega$  max

#### ■ HOUSING

- Part No. : JS-1142B-XX
- Poles : 2 - 18
- Material : PBT UL94V-0
- Q' ty : 1,000 pcs./Bag

Poles	Part No.	Dimensions(mm)	
		A	B
2	JS-1142B-02	2.54	5.08
3	JS-1142B-03	5.08	7.62
4	JS-1142B-04	7.62	10.16
5	JS-1142B-05	10.16	12.70
6	JS-1142B-06	12.70	15.24
7	JS-1142B-07	15.24	17.78
8	JS-1142B-08	17.78	20.32
9	JS-1142B-09	20.32	22.86
10	JS-1142B-10	22.86	25.40
11	JS-1142B-11	25.40	27.94
12	JS-1142B-12	27.94	30.48
13	JS-1142B-13	30.48	33.02
14	JS-1142B-14	33.02	35.56
15	JS-1142B-15	35.56	38.10
16	JS-1142B-16	38.10	40.64
17	JS-1142B-17	40.64	43.18
18	JS-1142B-18	43.18	45.72

**Allconnectors**

www.allconnectors.de  
 info@allconnectors.de  
 Tel.: 0049 711 7009503  
 Fax: 0049 711 7009504  
 70794 Filderstadt - Germany  
 Kettenerstr. 25

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	DATE	LTR	REVISION RECORD	DATE
林陳鏞	1:1	mm	.0 ±0.3	ECR	RoHS Compliant	06/04/01			
CHECKED BY	PROJ	VER NO.	.00 ±0.2	ECR	200705-020	07/05/31			
			.000 ±0.1	ECR	200706-014	07/06/12			
			ALL ±	ECR	200809-009	08/09/10			
			ANGLE						
			0° ±						
			.0° ±						
<b>PART NO</b>	<b>JS-1142B-XX</b>						<b>CUSTOMER</b>		
<b>2.54mm Crimp Style Connectors Housing</b>		黄科源	2008/09/10	A4			Conforms to The RoHS Instruction		