



Features:

- * Available in 2x2 through 2x40 Circuits
- * Material: P.B.T+15% GF UL94V-0
- * Accepts MCE-T-24 Crimp Terminal

Specification:

- * Pitch between Poles 2.54mm
- * Rated Voltage 250V AC,DC
- * Rated Current 2.5A
- * Withstand Voltage 1,000V AC/minute
- * Insulation Resistance 1,000M Ohms/min
- * Temperature Range $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$

Circuits	Part No	Dimension mm	
		A	B
2X2	MCE-H-2X02	2.54	9.68
2X3	MCE-H-2X03	5.08	12.22
A: 2.54 X (PART NO. OF PIN/2-1) B: 7.14 + A			
2X40	MCE-H-2X40	99.06	106.2

MCE-H-2Xxx-LF
LEADFREE

RoHS Compliant

All Connectors

www.allconnectors.com info@allconnectors.com
Tel: 0420 031 00000 Fax: 0420 031 00004
20794 Fuldbrook Germany ceter@allconnectors.com

PART NO. MCE-H-2Xxx

DWG NO. MCE-H-2Xxx

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIPTION:

2.54mm (.100") Pitch Housing

AREA

REVISIONS

HK

DATE