





ROHS




04P






06P




08P





10P



12P



14P



16P

■ Specifications:

- Voltage rating: 400V AC/DC
- Current rating: 14A AC/DC
- Withstanding voltage: 1800V AC/minute
- Temperature range: -40° C ~ +120° C
- Insulation resistance: ≥1000MΩ
- Wire range: 16~22AWG
- Plastic material: PA66 UL 94V-0
- Poles:4~16P

8350 H XX W 1 3 03
 ① ② ③ ④ ⑤ ⑥ ⑦

①Series:

②Title: H-HSG (Housing)

③Circuit number: XXP

④Category: W-Wire B-Board

⑤Color:

1-Black 2-Natural 3-Beige 5-Gray

⑥Plastic material:

2-PA9T 3-PA66 5-PA6T 7-PA46

⑦Special code:

03-Double row Left key

Poles	Dimensions	
	A	B
4	3.50	8.20
6	7.00	11.70
8	10.50	15.20
10	14.00	18.70
12	17.50	22.20
14	21.00	25.70
16	24.50	29.20

GENERAL TOLERANCE
 .X ±0.3
 .XX ±0.2
 .XXX ±0.1

Part NO:
 8350HXXW1303

TITLE:
 XXP 4.60X3.50mm Power Wire-D HSG Black

Allconnectors

www.allconnectors.de
 Tel.: 0049 711 7009503
 70794 Filderstadt - Germany

info@allconnectors.de
 Fax: 0049 711 7009504
 Kettnerstr. 25

2017/06/16


A

DATA EDITION

DESCRIPTION

DRAW

PROJECT



UNIT	SCALE	PAGE	EDITION
MM	1:1	1 OF 1	A

APPROVED	CHECK	DRAW	DATA	FILE NUMBER
----------	-------	------	------	-------------

Kuang LSTC-HS-000