


ROHS





04P




06P




$B \pm 0.30$
 $A \pm 0.25$



08P




10P



7.90 ± 0.15

3.50 ± 0.15

17.70




4.60 ± 0.15


9.50

11.10



14.15 ± 0.30



12P



14P



16P

■ Specifications:

- Voltage rating: 400V AC/DC
- Current rating: 8A AC/DC
- Withstanding voltage: 1000V AC/minute
- Temperature range: $-40^{\circ}C \sim +120^{\circ}C$
- Insulation resistance: $\geq 1000M\Omega$
- Wire range: 16~22AWG
- Plastic material: PAXX UL 94V-0
- Poles: 4~16P

8350 H XX W 1 3 05
① ② ③ ④ ⑤ ⑥ ⑦

①Series:

②Title: H-HSG (Housing)

③Circuit number: XXP

④Category: W-Wire B-Board

⑤Color:

1-Black 2-Natural

⑥Plastic material:

3-PA66 9-PA4T

⑦Special code:

05-Double row Right key with button

| Poles | Dimensions | |
|-------|------------|-------|
| | A | B |
| 4 | 3.50 | 8.20 |
| 6 | 7.00 | 11.70 |
| 8 | 10.50 | 15.20 |
| 10 | 14.00 | 18.70 |
| 12 | 17.50 | 22.20 |
| 14 | 21.00 | 25.70 |
| 16 | 24.50 | 29.20 |

GENERAL TOLERANCE

.X ± 0.3

.XX ± 0.2

.XXX ± 0.1

PROJECT



Part NO:

8350HXXW1305

TITLE:

XXP 4.60X3.50mm Power Wire-D HSG

UNIT
MM

SCALE
1:1

PAGE
1 OF 1

EDITION
A

Allconnectors

www.allconnectors.de
Tel.: 0049 711 7009503
70794 Filderstadt - Germany

info@allconnectors.de
Fax: 0049 711 7009504
Kettenerstr. 25

APPROVED CHECK DRAW DATA FILE NUMBER

Kuang

LSTC-HS-012

2017/06/16

A

DATA

EDITION

DESCRIPTION

DRAW