



1. 備注:

- 1). 外觀無缺料, 破損, 髒污
- 2). 材料: NYLON 66 UL 94V-0
- 3). 顏色: 本色

2. Dimension:

Circuits	Part No.	Dimension:(mm)		
		A	B	C
3	VU-H-03	13.55±0.25	7.92±0.20	11.54±0.20
4	VU-H-04	17.51±0.25	11.88±0.20	15.50±0.20
5	VU-H-05	21.47±0.30	15.84±0.25	19.46±0.25
7	VU-H-07	29.39±0.30	23.76±0.25	27.38±0.25

3. Specifications:

Current rating:	10A AC/DC
Voltage rating:	250V AC/DC
Temperature range:	-25°C to +85°C
Insulation resistance:	1000MΩ Min
Withstanding voltage:	1500V AC/DC
Terminal/Housing Retention Force:	2.5kgf Min

VU-H-xx-LF  
LEADFREE  
03:03WAY  
07:07WAY

RoHS Compliant

<p>www.allconnectors.com Tel.: 0049 711 4005003 70/94 Hilderstadt - Germany</p>	PART NO. VU-H-xx DWG NO. VU-H-xx FILE NO.	CHECKED BY CY DRAWING BY	TOLERANCES ARE X ± 0.2 .XX ± .XXX ± ANG	DESCRIPTION:			
	UNIT / mm    SCALE 1:1	PROJECTION		AREA	REVISIONS	HK	DATE