



**SPECIFICATIONS**

Current Rating: 1A AC,DC  
 Voltage Rating: 600V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max  
 Insulation Resistance: 1000MΩ Min  
 Withstanding Voltage: 1800V AC/minute  
 Material: Nylon66,UL94V-0  
 Color: Natural(White)

**Ordering Information & Dimensions**

PART NO.	Dimensions	
	A	B
BH-H-02	4.00	9.80
BH-H-03	8.00	13.80
BH-H-04	12.00	17.80
BH-H-05	16.00	21.80

BH-H-xx-LF  
 LEADFREE  
 RoHS Compliant

**All Connectors**  
 www.allconnectors.de  
 Tel.: 0049 711 7009503  
 70794 Filderstadt - Germany

info@allconnectors.de  
 Fax: 0049 711 7009504  
 Kettnerstr. 25

PART NO. BH-H-xx		CHECKED BY CY		TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIPTION: 4.00mm PITCH HOUSING	AREA	REVISIONS	HK	DATE
DWG NO. BH-H-xx		DRAWING BY							
FILE NO.		PROJECTION							
UNIT / mm	SCALE 1:1								