



PCB LAYOUT

SPECIFICATIONS

Pitch: 4.14
 Applicable wire: AWG#28~#22
 Voltage rating: 250V DC/AC(rms)
 Current rating: 10.0A
 Withstand voltage: 1500V AC(rms)
 Working Temperature: -25°C~+85°C
 Insulations resistance: $\geq 1000M\Omega$
 Contact resistance: $\leq 0.015\Omega$
 Applicable PC board thickness: 1.6mm

MATERIAL

Housing: Nylon66 UL94V-0
 Pin header:
 Water: Nylon66 UL94-0V
 Pin: Brass
 Terminal: Phosphor bronze
 Contact Plating: Tin over Ni

备注:

1. 塑胶颜色为乳白色
(按照客户提供样品颜色更改)!
2. IQC来料检验按客户样品比对检验,
以不出现色差为准!

Allconnectors

E				Units	mm	Scale	3:1	Drawing By	Date	www.allconnectors.de		info@allconnectors.de			
D		更改尺寸 (D1) (D2) (D3) (D4)		03/03-09		Tolerance Unless Otherwise Specified		Check By		Date	Tel.: 0049 711 7009503		Fax: 0049 711 7009504		
C				10/01-09				Date		2008/06/04	70794 Filderstadt - Germany		Kettenerstr. 25		
B		改变塑胶颜色(按照客户样品更改)		07/21-08		.X ~ ±0.30		Sheet		1 of 1	Title		4.14*4.14 针座/90度		
A		RELEASED		06/04-08		.XX ~ ±0.25		Approval By		Date	Thirt Angle Projection		Drawing No.	LY-4.14-2X6MR	REV
REV	ZONE	LTR	DESCRIPTION.	ECN.NO.	Date	.XXX ~ ±0.20		File Path		E/:CAD/ZZ				D	
						Angle ~ ± 3°									