






2X01P



2X2-2X12P



2X1P

SPECIFICATIONS:
 Voltage Rating: 600V AC / DC
 Current Rating: 9A AC / DC
 Withstanding Voltage: 1500V AC/minute
 Temperature Range: -25°C~+85°C
 Insulation Resistance: ≥1000MΩ
 Contact Resistance: ≤10mΩ
 After Environmental Testing: ≤20mΩ
 *Mates with C4255 series Wafer


Material: Nylon 66, UL94V-2(0), Natural&Black

C4255 HF -2NP- XX XX
 ① ② ③ ④ ⑤

- ① Series No.
- ② Plastic Shell Category: HF-Male Housing,
- ③ Circuit No.: 208~2x04PIN
- ④ Material: N0-Nylon66, UL94V-0,
N2-Nylon66, UL94V-2
- ⑤ Color: BK-Black, NA-Natural ,

Ordering Information& Dimensions

Poles	Dimensions (mm)	
	A	B
2*1P	—	5.70
2*2P	4.20	9.60
2*3P	8.40	13.80
2*4P	12.60	18.00
2*5P	16.80	22.20
2*6P	21.00	26.40
2*7P	25.20	30.60
2*8P	29.40	34.80
2*9P	33.60	39.00
2*10P	37.80	43.20
2*11P	42.00	47.40
2*12P	46.20	51.60

								料号 PART NO C4255HF-2NP-XXXX					
						www.allconnectors.de Tel.: 0049 711 7009503 70794 Filderstadt - Germany		info@allconnectors.de Fax: 0049 711 7009504 Kettenerstr. 25					
						核准 APPD	审核 CHK	绘图 DR	日期 DATA	品名 TITLE 4.2mm Crimp Style connectors			
日期 DATE	旧版次 OLD REV	新版次 NEW REV	变更内容 DESCRIPTION	审核 CHK	核准 APPD	Rodney	兰雄	Lce	2015-07-14	单位 UNIT MM	比例 SCALE 1/1	图号 NUMBER 81002	版次 REV A

一般公差
 GENERAL TOLERANCE
 .X ±0.3
 .XX ±0.2
 .XXX ±0.1

