



■ SPECIFICATIONS :

- Voltage Rating: 250V AC / DC
 - Current Rating: 7A AC / DC
 - Withstanding Voltage: 1500V AC/minute
 - Temperature Range: -25° C~+85° C
 - Insulation Resistance: 1000MΩ Min.
 - Contact Resistance: 10mΩ Max.
 - Wire Range: AWG#18~22
- *Used in C4255HF series Housing

■ Material:

- Terminal: Brass
- Finish: Tin plated or Gold flash

C4255 T F X - B XX
 ① ② ③ ④ ⑤ ⑥

① Series: C4255

② T-Terminal

③ Terminal Type: M-mate with female housing
 F-Mate with male housing
 W-WAFER mate with wafer

④ Feature Type: Blank-Normal M-Middle H-High

⑤ Material: P-Phosphor Bronze, B-Brass

⑥ Plating Specification: T1-Tin Plated G1-Gold flash
 GT-Contact Gold Flash Bottom Nickel

Ordering Information & Specifications

Part No	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
C4255TF-BT1	AWG#18-#22	3.00mm(max)	Brass	Tin-plated	10,000pcs
C4255TF-BG1	AWG#18-#22	3.00mm(max)	Brass	Gold flash	10,000pcs
C4255TF-BGT	AWG#18-#22	3.00mm(max)	Brass	Contact Gold Flash Bottom Nickel	10,000pcs

								料号 PART NO					
						www.allconnectors.de Tel.: 0049 711 7009503 70794 Filderstadt - Germany		info@allconnectors.de Fax: 0049 711 7009504 Kettnerstr. 25		C4255TF-BXX			
						核准 APPD		审核 CHK		绘图 DR		日期 DATA	
						Rodney		兰雄		Lce		2014/11/04	
						角法 PROJECT		单位 UNIT		比例 SCALE		图号 NUMBER	
								MM		1/1		版次 REV 38003 A	
日期 DATE	旧版次 OLD REV	新版次 NEW REV	变更内容 DESCRIPTION			审核 CHK	核准 APPD						