



A-A SEC



B-B SEC



C-C SEC

■ SPECIFICATIONS

- Voltage rating: 250V AC, DC
- Current rating: 7A, AC, DC
- Withstanding Voltage: 1500V AC/minute
- Insulation resistance: 1000M min
- Temperature range: -85° C ~ +105° C (Including temperature rise in applying electrical current)
- Applicable PC board thickness: .063" (1.6mm)
- Contact resistance: Initial Value/10m max
After environmental testing/20m max

■ TERMINAL

- Part No.: 4256T
- Applicable wire: AWG#18-24
- Material: Brass
- Finish: Tin plated
- Thickness: 0.2mm
- Q ty: 10000pcs/roll

All Connectors

www.allconnectors.eu | info@allconnectors.eu
Tel. +49 (0)711 / 358 110 20 | Fax +49 (0)711 / 358 110 25

APPROVED BY	DATE	SCALE	TOLERANCE	
	2007/08/31	4:1	.0	±0.3
CHECKED BY	UNIT	VIEW	.00	±0.2
	mm		.000	±0.1
DRAWN BY	VER NO.	SIZE	.0	±
	D1	A4	.0	±
			ANGLE	
			A-011	

PART NO MF-4256T

4.2mm Crimp Style connectors