



■ SPECIFICATIONS

- Voltage Rating: 250V AC, DC
- Current Rating: 7A, AC/ DC
- Withstanding Voltage: 1500V AC/minute
- Insulation Resistance: 1000M min
- Temperature Range: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
- Contact resistance: 20m max

■ HOUSING

- Part No.: MF-9357-1*XX
- Poles: 02-12
- Material: Nylon 66 UL 94V-0 or UL94V-2
- Q'ty: 1000pcs/bag

Poles	Part No	Dimensions (mm)	
		A	B
2	9357-1*02	4.20	9.60
3	9357-1*03	8.40	13.80
4	9357-1*04	12.60	18.00
5	9357-1*05	16.80	22.20
6	9357-1*06	21.00	26.40
7	9357-1*07	25.20	30.60
8	9357-1*08	29.40	34.80
9	9357-1*09	33.60	39.00
10	9357-1*10	37.80	43.20
11	9357-1*11	42.00	47.40
12	9357-1*12	46.20	51.60

Allconnectors

www.allconnectors.eu | info@allconnectors.eu
Tel. +49 (0)711 / 358 110 20 | Fax +49 (0)711 / 358 110 25

PART NO

MF-9357-1*XX

4.2mm Crimp Style connectors

APPROVED BY

DATE

SCALE

TOLERANCE

2007/05/15

4:1

.0 ±0.3

CHECKED BY

UNIT

VIEW

.00 ±0.2

DRAWN BY

VER NO.

SIZE

.000 ±0.1

D1

A4

ANGLE

.0 ±

.0 ±