



## ■ SPECIFICATIONS

- Voltage Rating: 250V AC, DC
- Current Rating: 7A, AC/ DC
- Withstanding Voltage: 1500V AC/minute
- Insulation Resistance: 1000M  $\Omega$  min
- Temperature Range: -40°C~+105°C
- Contact resistance: 20m  $\Omega$  max

## ■ HOUSING

- Part No.: MF-9357-2\*XX
- Poles: 2-24
- Material: Nylon 66 UL 94V-2 or UL94V-0
- Q'ty: 1000pcs/bag

Poles	Part No	Dimensions (mm)	
		A	B
2	9357-2*01	--	5.50
4	9357-2*02	4.20	9.70
6	9357-2*03	8.40	13.90
8	9357-2*04	12.60	18.10
10	9357-2*05	16.80	22.30
12	9357-2*06	21.00	26.50
14	9357-2*07	25.20	30.70
16	9357-2*08	29.40	34.90
18	9357-2*09	33.60	39.10
20	9357-2*10	37.80	43.30
22	9357-2*11	42.00	47.50
24	9357-2*12	46.20	51.70

# Allconnectors

www.allconnectors.eu | info@allconnectors.eu  
Tel. +49 (0)711 / 358 110 20 | Fax +49 (0)711 / 358 110 25

PART NO MF-9357-2\*XX

4.2mm Crimp Style connectors

APPROVED BY	DATE	SCALE	TOLERANCE	
	2007/04/16	4:1	.0	±0.3
CHECKED BY	UNIT	VIEW	.00	±0.2
	mm		.000	±0.1
DRAWN BY	VER NO.	SIZE	ANGLE	
	01	A4	.0	±
			.0	±
			A-007	